NRO RE\	(/IEW COMP ∆हांगि€ो 0ed For Relea	CLASSIFIED MESS. se 2002/10/31 T CIA-RDP	70B00783R	000100130031	outing out
DATE	: 1930Z 26 OCT 60	SECRET	. 3	chibb.	6 Fin
· Verilian	A CONTRACTOR OF THE PROPERTY OF THE CONTRACTOR O			n Melakupanian da radi dan baja Penjada 19 Alianagkan da ada da	AI.
or McD3	25X1A	eren eren eren eren eren eren eren eren	A Company		Marin and a supplementation of the Control of the C
	DPD (1,2,3,4,5,6,7,8,9	CIRCULATE X-REF	INITIAL	ROUTINW	Parada Parad Parada Parada Parad
1N7 O	:S/C (11)	GB -	Section 1 of the Control of the Cont	PELA COMPLETO, EMPLETO MENTINATORIA PER	The second secon
25X1A	EG TOR: 2014Z 26 OCT 60		-	25X1A	IN 35390
Ţē		3F0		Corre	330 NRO
•	ATT:	DITT			
25X1A 25X1A		25) 177 (IN 35243	- /-		·

- 1. TO OBTAIN MORE ACCURATE INFORMATION ON PAYLOAD CONSUMPTION,
 A DIGIPOT APPROACH SEEMS REASONABLE, HOWEVER, FCIC DOES NOT SHARE
 THE SAME CONFIDENCE IN THE SUGGESTED LOCATION OF INSTALLATION. SINCE
 THE SUPPLY METERING ROLLER IS A POSITIVE DRIVE OFF OF THE CAMERA
 MOTOR, IT IS AN UNRELIABLE INDICATION OF PAYLOAD CONSUMPTION.
 CAMERA MOTOR, AND THEREFORE, SUPPLY METERING CAN BE OPERATING IN THE
 ABSENCE OF PAYLOAD.
- 2. A MORE LOGICAL LOCATION FOR A FILM FOOTAGE TRANSDUCER WOULD BE IN THE CASSETTE PROPER. THIS WOULD, HOWEVER, NECESSITATE SOME CHANGES TO THE FILM HANDLING CHARACTERISTICS WHICH WOULD REQUIRE ADDITIONAL TESTING TO ASSURE RELIABILITY. SUCH AN APPROACH IS SOUND BUT REQUIRES A LITTLE TOO MUCH TIME AND EFFORT AND FOR THIS REASON IS NOT RECOMMENDED BY FCIC.
 - 3. A SIMPLE AND UNCOMPLICATED APPROACH WOULD BE TO TELEMETER

SECRET

REPRODUCTION BY OTHER THAN THE ISSUING OFFICE IS PROHIBITED.

SE THE REPORT OF THE PROPERTY HAVE BEEN AND THE WAY THE PROPERTY OF THE PROPER

25X1A

SIGNAL NOW EXISTS AS A NORMAL TEST FUNCTION IN THE LAB BUT DOES NOT HAVE TELEMETERY CAPABILITIES. AS A SUGGESTED METHOD OF UTILIZING THIS FUNCTION, IT IS PROPOSED THAT THE SCAN PULSE SIGNAL DRIVE A DIGIPOT SUCH AS THE PHOTOCON UNIT WHICH WAS INVESTIGATED AS A REPLACEMENT FOR THE PRESENTLY USED DIGITOTE. KNOWING THE TOTAL NUMBER OF SCAN CYCLES, IT WOULD BE A SIMPLE MATTER TO DERIVE TOTAL FOOTAGE TO AN EXTREMELY HIGH DEGREE OF ACCURACY. SUCH AN APPROACH OFFERS SIMPLICITY IN THAT THE SCAN PULSE SIGNAL ALREADY EXISTS AND DOES NOT IN ANY WAY AFFECT FILM HANDLING CHARACTERISTICS. THE COUNT RATE REQUIREMENTS OF SUCH A SYSTEM IS NOT AT ALL DEMANDING OF TELEMETERY COMMUTATION IN THE COUNTER AND WOULD BE CONSIDERED A SIMPLE PROBLEM REQUIRING A MINIMUM OF ENGINEERING EFFORT.

4. THE SYSTEM SUCH AS PROPOSED IN PARA 3 WOULD REQUIRE 25X1A APPROXIMATELY 8 WEEKS TO IMPLEMENT AT A BUDGETARY ESTIMATE OF

|--|

END OF MESSAGE